

# GT5000

## “Presenting” the GT5000 Series TTW ATM

Genmega introduces the **GT5000** series ATM. A high performance yet economical **Through-The-Wall ATM** solution with the look and feel of a full bank ATM. Designed for wall or Kiosk installation, the **GT5000** series makes new TTW installation or replacements a snap. Built with the same compact modular components as your existing Genmega machines and engineered for easy installation and reliable operation. The **GT5000** includes high-end features like a 15” High Bright LCD which support custom advertisements and a 3-cassette cash dispenser with motorized cash presenter. A new Touch-Screen rear-service panel allows convenient and safe access for ATM Operators and Service personal.

The **GT5000** series ATM is ADA compliant and Chip Card (EMV) ready, including a PCI / Interac certified encrypting PIN pad (EPP), a voice guidance system, and lighted action indicators (including lighted keypad). Features of a high end **Through-The-Wall ATM** with the low maintenance and reliability that Genmega delivers makes this an excellent TTW solution.



# GT5000

## Integrated Illuminated Topper Sign

High Visibility LED Sign  
Attract Customers

## LCD Screen

15 inch color TFT-LCD Panel  
High bright LED backlight (800cd/m<sup>2</sup>)  
1024 x 768 (XGA) Resolution

## Printer

80mm/3" Receipt Printer  
200DPI monographic printing

## PIN Entry Device

16-key alpha numeric keypad  
PCI / Interac Certified  
Triple-DES (TDES) EPP

## Rear Service Panel

7 inch color touch screen  
Backlit TFT LCD panel  
800 x 480 Resolution

## Communication

56Kb Internal Modem  
TCP/IP Ethernet - SSL



## CPU

Cortex-A8 32-bit CPU  
DDR2 256MB RAM / WinCE 6.0 OS

## ADA

Voice Guidance  
Lighted Transaction Guidance  
Accessible Keypad Layout

## Card Reader

DIP Style Magnetic Card Reader  
EMV - Optional

## Security

UL291 Business Hours Vault  
Electronic Lock or Cencon (optional)

## Cash Dispenser

1 x 1700 Note Cassette  
2 x 1700 Note Multi-Cassette  
3 x 1700 Note Multi-Cassette  
Presenter Module

## Dimensions

Height = 56.7"  
Width = 24.1"  
Depth = 33.9"  
Weight = 570 lbs

## Operating Environment

Temperature range : 40°F - 95°F  
Relative humidity : Non-condensing=15%-85%

## Power Requirements

110/220 VAC ± 10%, 50/60 Hz, 145 Watts

